

- 1- BFGoodrich® Brand Logo
- 2- Free space for hot branding
- 3- Tire construction. In this case, 4 steel plies in the tread
1 steel ply in the sidewall
- 4- USA regulation
Max load per tire
Single and Dual, Kd and Lbs.
Max Pressure per tire
Single and Dual, kPa and psi.
- 5- FRT marking (Free Rolling Tire) Tire for trailer only
- 6- M+S : Mud and Snow Rating
- 7- Tread Design Name (Route Control)
- 8- REGROOVABLE : Tire can be regrooved
- 9- Warning : provides user important safety information
- 10- TUBELESS : Radial construction of the tire,
no inner tube.
- 11- Tire sizing : 385/65R22,5,
385 – Nominal cross section width (mm)
65 (aspect ratio : sidewall height = 65%
tire section width, R – Radial,
22.5 –Wheel size (in)
- 12- Manufacturing location: indicates
Where the tire was manufactured.
- 13- DOT : Department of Transportation code
020X Plant Code
The last 4 numbers indicate the tire
manufacturing date: 1014 for instance
Week 10, year 2014
- 14- BFGoodrich® Tires Nomenclature :
D for drive,
S for steer, and
T for trailer.
- 15- European regulation marking : required to
prove the tire is allowed to operate in
Europe/
- 16- Load Index (here 160) and Speed index (here K) :
Load and speed capacity of the tire.
- 17- PR : Ply Rating, here 20

