

BFGoodrich Highway Control S2

AN ALL-POSITION TIRE DESIGNED TO DELIVER LONG, EVEN WEAR AND FUEL EFFICIENCY TO KEEP YOUR FLEET UP AND RUNNING FOR THE LONG HAUL.




Directional Tire
(For 1st Half of Life)

business.bfgoodrichtires.com

BFGoodrich
Tires

BFGoodrich Highway Control S2



GO THE DISTANCE

The BFGoodrich Highway Control S2 tire is a durable all-position tire built for long tread life and dependable performance, designed to keep fleets running smoothly over the long haul.

LONG TREAD LIFE

Expect long tread life and exceptional even wear performance.

- Designed with a wider, deeper tread to deliver more miles than its predecessor, the BFGoodrich ST244 tire.
- Shoulder decoupling groove with micro sipes and directional tread pattern help fight the onset of irregular wear.



MULTIPLE RETREAD LIVES

Legendary BFGoodrich casing.

- Excellent retreadability
- Durability keeps you up and running.

5 YEAR⁽¹⁾

5 Year / 2-Retread Manufacturer's Limited Casing Guarantee

(1) 5 Year / 2-Retread Limited Casing Guarantee when retreaded by an authorized Michelin Retread Technologies (MRT) Dealer or an Oliver Retread dealer. Full list of terms and conditions can be found [HERE](#).



FUEL EFFICIENCY

New sidewall shape designed to improve fuel economy.



EVEN WEAR OVER THE LONG HAUL

If you are not completely satisfied with the BFGoodrich Highway Control S2 tire mileage performance in the first year or before 50% of its usable tread life – whichever comes first – we will reimburse 50% of your acquisition price per tire.⁽²⁾

For full list of terms and conditions, click [HERE](#).



Size	Load Range	Catalog Number	Tread Depth (32nds)	Max. Speed (3)		Loaded Radius		Overall Diameter		Overall Width (4)		Approved Wheels (Measuring wheel listed first)	Min. Dual Spacing (4)		Revs Per Mile	Max Load Per Tire Single				Max Load Per Tire Dual			
				mph	km/h	in.	mm.	in.	mm.	in.	mm.		in.	mm.		lbs.	psi	kg.	kPa	lbs.	psi	kg.	kPa
11R22.5	G	34551	19	75	120	19.2	489	41.2	1047	11.2	284.47	8.25, 7.5	12.5	318	503	6175	105	2800	720	5840	105	2650	720
11R22.5	H	20040	19	75	120	19.3	491	41.3	1048	11.2	284.3	8.25, 7.5	12.5	318	501	6610	120	3000	830	6005	120	2725	830
295/75R22.5	G	96370	19	75	120	18.7	474	40.0	1015	10.9	277.5	8.25, 9.0	12.5	318	518	6175	110	2800	760	5675	110	2575	760
295/75R22.5	H	70978	19	75	120	18.6	473	40.1	1018	11.3	285.8	8.25, 9.0	12.8	326	517	7160	123	3250	850	6610	123	3000	850
11R24.5	H	07873	19	75	120	20.3	515	43.3	1099	11.2	284.7	8.25, 7.5	12.5	318	483	7160	120	3250	830	6610	120	3000	830

Note: Wheel listed first is the measuring wheel.

(1) 5 Year / 2-Retread Limited Casing Guarantee when retreaded by an authorized Michelin Retread Technologies (MRT) Dealer or an Oliver Retread dealer. Full list of terms and conditions can be found [HERE](#).

(2) For full list of terms and conditions, click [HERE](#).

(3) Exceeding the lawful speed limit is neither recommended nor endorsed.

(4) Tire section widths and overall widths will change 0.1 inch (2.5 mm) for each 1/4 inch change in wheel width. Minimum dual spacing should be adjusted accordingly. BFGoodrich tires are subject to a continuous development program.

BFGoodrich Commercial Truck Tires reserves the right to change product specifications at any time without notice or obligation.

MNA, Inc. continually updates its product information to reflect any changes in Industry Standards. Printed material may not reflect the current Load and Inflation information. Please visit business.bfgoodrichtires.com for the latest product information. The actual load and inflation pressure used must not exceed the wheel manufacturer's maximum conditions. Never exceed a wheel manufacturer's limits without permission from the component manufacturer.

Application	Highway	Regional	Urban	Coach/Bus	On/Off-Road

Position	Steer	Drive	Trailer

Recommended Application Acceptable Application

» Take control today at:
business.bfgoodrichtires.com

To Find Your Nearest BFGoodrich Commercial Truck Tire Dealer
Call: United States, 1-877-788-8899; Canada, 1-888-871-6666
Or Visit: business.bfgoodrichtires.com